NPS ARCHIVE
1949
GOOCH, F.

Thesis
G55

Library
U. S. Naval Postgraduate School
Monterey, California

PHP
7,11-2000

THE UNIVERSITY OF OKLAHOMA
GRADUATE COLLEGE

A STUDY OF THE EFFECT OF VISCOSITY RATIO ON THE DISPLACEMENT OF MISCIBLE FLUIDS IN POROUS MEDIA

A THESIS
SUBMITTED TO THE GRADUATE FACULTY
in partial fulfillment of the requirements for the
degree of
MASTER OF PETROLEUM ENGINEERING

BY
Floyd Warren Dodson, Jr.
Norman, Oklahoma

1949

949
GOOCH, F.

G55
c.2

Library
U. S. Naval Postgraduate School
Monterey, California

A STUDY OF THE EFFECT OF VISCOSITY RATIO ON THE
DISPLACEMENT OF MISCIBLE FLUIDS IN POROUS MEDIA

A THESIS

SUBMITTED FOR THE DEPARTMENT OF PETROLEUM ENGINEERING

BY_____

_____

_____

ACKNOWLEDGMENTS

The writer wishes to express his appreciation to Dr. John C. Calhoun, Jr., for his guidance, assistance and helpful suggestions in carrying out this investigation.

Appreciation is also expressed to the Petroleum Engineering Faculty, who helped in editing this thesis and to his fellow workers for their helpful suggestions.

Grateful acknowledgment is made to the U.S. Naval Postgraduate School for making possible this research.

TABLE OF CONTENTS

		Page
LIST OF TABLES		v
LIST OF ILLUSTRATIONS		vi
Chapter		
I.	INTRODUCTION	1
II.	REVIEW OF PREVIOUS INVESTIGATIONS	3
III.	STATEMENT OF PROBLEM	6
IV.	MATERIALS	8
V.	EXPERIMENTAL APPARATUS	12
VI.	EXPERIMENTAL PROCEDURE	15
	Permeability Determinations	15
	Porosity Determinations	16
	Index of Refraction Measurements	17
	Experimental Runs	17
VII.	ANALYSIS OF DATA	45
	Theoretical Approach	46
	Sample Calculations	47
	Discussion of Experimental Results	48
	Errors Involved	56
VIII.	SUMMARY	58
IX.	CONCLUSIONS	60
BIBLIOGRAPHY		62

[illegible] . . . . . [illegible]

[illegible] . . . . . [illegible]

[illegible]

I. [illegible] 1

II. [illegible] 2

III. [illegible] 3

IV. [illegible] 5

V. [illegible] . . . . . [illegible]

VI. [illegible] 13

[illegible] 15

[illegible] 17

[illegible] 19

[illegible] 21

VII. [illegible] 25

[illegible] 27

[illegible] 29

[illegible] 29

[illegible] 30

VIII. [illegible] 33

IX. [illegible] 36

[illegible] 43

LIST OF TABLES

Table		Page
1.	Run Number 1	18
2.	Run Number 2	20
3.	Run Number 3	21
4.	Run Number 4	22
5.	Run Number 5	23
6.	Run Number 6	24
7.	Run Number 7	25
8.	Run Number 8	26
9.	Run Number 9	27
10.	Run Number 10	28
11.	Run Number 11	29
12.	Composite Data	30

LIST OF ILLUSTRATIONS

Figure		Page
1.	A Linear Waterflood System, after Buckley	31
2.	Fluid Flow Diagram	32
3.	Effluent Composition vs Pore Volume Produced, (Horizontal Position)	33
4.	Effluent Composition vs Pore Volume Produced, (Vertical Position)	34
5.	The Effect of Pressure on Displacement	35
6.	The Effect of Gravity on Displacement	36
7.	Data vs Pore Volume Produced	37
8.	Data vs Pore Volume Produced	38
9.	Efficiency of Recovery at One Pore Volume as a Function of Viscosity Ratio	39
10.	Efficiency of Recovery at Break Through as a Function of Viscosity Ratio	40
11.	A Comparison to Leverett and Buckley Data on Efficiency of Initial Phase of Production	41
12.	Pore Volumes Produced at Complete Recovery vs Viscosity Ratio	42
13.	Semi-Log Plot of Pore Volumes Produced at Complete Recovery	43
14.	Viscosity Chart	44

Figure		Page
1a.	[illegible]	32
1b.	[illegible]	[illegible]
2a.	[illegible]	33
2b.	[illegible]	34
3a.	[illegible]	35
3b.	[illegible]	36
4a.	[illegible]	37
4b.	[illegible]	38
5a.	[illegible]	39
5b.	[illegible]	40
6a.	[illegible]	41
6b.	[illegible]	42
7a.	[illegible]	43
7b.	[illegible]	44

A STUDY OF THE EFFECT OF VISCOSITY RATIO ON THE DISPLACEMENT OF MISCIBLE FLUIDS IN POROUS MEDIA

CHAPTER I

INTRODUCTION

Within recent years the increasing demand for petroleum products and the realization that the supply of new sources of petroleum is not inexhaustible have focused attention on the fact that in most of our oil production in the past, only about one third of the oil originally present in the reservoir is recovered when the economic limit is reached. This figure applies only when the field is produced by conventional methods where the main source of energy is the gas dissolved in the oil.

With this in mind many investigators have sought to find ways both to remove the residual oil and to improve methods of production so that a much greater per cent of the oil is removed initially.

Two methods are in common use today to remove the residual oil after primary depletion. Both of these methods involve displacement of the residual oil by another fluid. In one method gas and the other method water is used as the

displacing fluid. Although both of these methods have been applied in the field for a number of years and much laboratory work has been done on the displacement of oil by another fluid in a porous media, there still remains a large number of problems to be solved before the mechanics of displacement of fluids in a porous media is completely worked out. Many investigators are now working on these problems with the idea of gaining more complete recovery of petroleum from the reservoir.

CHAPTER II

REVIEW OF PREVIOUS INVESTIGATIONS

The initial study of flow of liquids through sands dates back to 1856 when H. d'Arcy (1)* performed his experiments on the flow of water through sand. In 1898 King (2) measured the rate of flow of water and air through consolidated and unconsolidated sands and published the results. It was not until 1920, when the increasing demand for oil caused the U.S. Bureau of Mines to make a series of experiments on flow characteristics of oil and water, that additional work was done on flow of fluids in a porous media. By 1930 the importance of flow measurements to production of gas and oil was realized and in the ensuing years the investigations of Cloud (3), Putting (4), Wyckoff, Botset and Muskat (5), and many others added materially to our knowledge of fluid flow in porous media.

In the last ten to fifteen years most of the work has been directed toward the development and improvement of methods of predicting petroleum reservoir performance. As a result there have been numerous investigations made of the behavior of immiscible fluids in porous media. Leverett (6),

---

*Numbers in parenthesis refer to references in the bibliography.

Leverett and Irwin (7), and others have contributed much to the development of the theory and mechanics of the displacement of oil by water. Information concerning the displacement of oil by gas was reported by several investigators such as Reid and Huntington (9), Botset (6), and Buckley and Leverett (10). The latter worked out a satisfactory picture of the mechanics of the displacement of oil by both water and gas.

However, while the above work was being carried out with immiscible fluids, little work was done on the mechanics of displacement of two miscible fluids. Botts (11) and Dunkar (12) investigated the effects of specific gravity, velocity and pressure on the amount of mixing taking place during the displacement of one gas by another in unconsolidated sand. They concluded that the amount of mixing was inversely proportional to the rate of flow and that it became less as the pressure was increased up to a certain point for any given linear velocity. Above this point an increase in pressure caused an increase in the amount of mixing. Their experiments also indicated that less mixing took place when the heavier gas was used the displacing fluid.

Russel, Morgan and Hubbert (13) in studying the mobility of interstitial waters arrived at some conclusions concerning the displacement of water by water in a unconsolidated sand. Their results in all cases showed that after injecting into the core a volume of displacing water equal to one pore

CHAPTER III

STATEMENT OF PROBLEM

This problem was undertaken to study the displacement of one fluid by another miscible fluid in a porous media. As in all problems of fluid displacement there are several variable factors involved. These factors are:

(1) Physical characteristics of the porous media

(2) Chemical characteristics of the porous media

(3) Viscosity of the fluids

(4) Specific gravity of fluids

(5) Differential pressure or rate of displacement

Since the experiment was undertaken primarily to obtain information of a fundamental nature it was thought best to vary only one factor and to maintain all other factors constant. Then it became evident during the course of this investigation that the force of gravity was affecting the results due to the displacement taking place with the core in a horizontal position, a series of similar drives were made with the core in a vertical position to determine the magnitude of the gravity effect.

This investigation was prompted by the fact that

CHAPTER IV

MATERIALS

The synthetic core that was used in this work consisted essentially of pure quartz grains partially consolidated by silica. This core was contained in a cylindrical lucite tube, 100 centimeters in length and 6.35 centimeters inside diameter.

To make this core Oil Creek sand, obtained from an outcrop near Sulphur, Oklahoma, was sieved and a fraction between 50 and 140 mesh retained. This sand was thoroughly washed with hot water then cleaned by agitation in hot hydrochloric acid. Following this it was again washed with water then agitated in a hot sodium hydroxide solution with a final wash with water until the solution was shown by litmus paper to be neutral. The sand was then placed in an oven to be dried. After drying was complete the sand was sieved with the 50 to 140 mesh fraction again retained.

Next the lucite tube was fitted with square end plate cut from one inch sheet lucite. A circular groove 3/16 inch deep, 6.35 centimeters inside diameter, and 7.73 centimeters outside diameter was machined in the face of each block and

a hole drilled and tapped for 3/8 inch threads in the center. Brass fittings and valves were threaded into these holes and a 130 mesh screen placed over the hole. The four corner of the two end plates were drilled to accommodate the rods. Next a neoprene rubber gasket was put into the groove of one end plate and two tie rods were placed in opposite corners. This plate was fitted to one end of the lucite tube, the two tie rods being secured at the other end in a wooden block placed on the lucite tube. Prior to putting on this block a 2 inch extension of the same diameter tube was placed on the end of the long tube. The block left this end of the tube partially open. The tube was then placed on a vibrating table in a vertical position with the end plate down and a length of rubber hose run from the brass fitting to a large beaker.

With the valve at the lower end closed Syton,* a colloidal suspension of silica in water, was poured into the top of the tube until there was approximately 3 inches of Syton in the tube. The cleaned sand was placed in a funnel which was clamped above the vertical tube. This allowed the sand to be fed slowly into the tube. Additional Syton was added to maintain its level approximately 3 inches over the sand as it was deposited into the bottom of the tube. This method was used to get uniform permeability and porosity in the core.

When the sand had been deposited even with the top of the long tube, the vibrating table was stopped, the tie rods

---

*Obtainable from the Nalco Chemical Co., Boston, Mass.

loosened and the extension tube removed. The other end plate was put on and all four tie rods run through both end plates and pulled tight, thus sealing both ends of the tube. With the core still in the vertical position the valve on the lower end was opened and the liquid drained out. Then dry air was forced into the top and passed down through the sand and out the lower end of the tube thus displacing any remaining water and drying out the sand. After twenty-four hours of drying with air, the bottom valve was closed, a vacuum pump attached to the top of the tube and a vacuum placed on the tube for twenty-four hours. At the end of this time approximately 1300 cubic centimeters of alcohol ("Synasol") was forced into the core through the lower end. The core was again dried by passing dry air through it for a period of forty-eight hours and then maintaining a vacuum on it for twenty-four hours.

The above procedure resulted in a partially consolidated core of essentially pure silica. At this time a series of permeability tests were run with air on the core. These indicated an average overall permeability of 3.4 darcies. However, upon installing pressure taps every 33.3 centimeters along the core it was found that one end of the core had a low permeability compared to the other two sections. A piece 6.3 centimeters long was removed from this end of the core and air permeabilities again run. The overall permeability was found to be 3.22 darcies and none of the sections deviated more than 3 per cent from this value. Since this gave a

fairly uniform core it was deemed satisfactory for the experiments to be run on it.

The porosity of the core was determined next. The first method was to measure pressure at two different values and record the volume removed in going from the higher to the lower pressure. By using the perfect gas law the porosity was calculated to be .337. The other method was by the use of wet and dry weights. The fractional porosity in this case was calculated to be .307. This latter value was used in all calculations since it was felt that the method used in calculating this value was far more accurate.

The sugar solutions used in this work were made with distilled water and commercial cane sugar (sucrose). The index of refraction of the distilled water was checked before the addition of the sucrose, then after addition of sucrose the index of refraction was again taken and from this information the per cent of sucrose in the solution was calculated and thus the viscosity known.

CHAPTER V

EXPERIMENTAL APPARATUS

With the core partially consolidated and its permeability and porosity judged sufficiently homogeneous for this experiment, additional holes were drilled and tapped in the tops of the end plates and brass fittings were installed. With the core in the horizontal position, a copper spigot was installed at the outlet end, and a brass tee installed at the inlet end. With brass valves installed on both sides of the tee a means was provided for purging the fluid system before it entered the core. Manometer leads were connected to the fittings on both end plates.

Next a 2½ liter pyrex bottle with a bottom outlet was set up with a rubber stopper that had a hole in the center through which a copper tube extended into the bottle to a point near the bottom of the bottle. The tube and stopper were held in place by a metal fitting fastened to the bottle by fine copper wire. A brass tee was connected to the tubing before it entered the bottle and from one side of this tee copper tubing was run to a source of air. Air originally under 100 psi pressure was first reduced by a pressure

regulator to 60 psi. It was further reduced and regulated by a Schlumbin Pressure Regulator which allowed a fine accurate control of the pressure over a range of 2 psi to 50 psi.

From the other side of the tee a lead was run to a mercury manometer. This measured the pressure existing at the end of the copper tubing in the bottle. Therefore, differences in fluid level in the bottle at various times during the runs would not affect the pressures placed on the system and a constant pressure could be maintained.

Since the level of the outlet of the copper tube in the bottle was adjusted to the same level as that of the inlet to the core, with a fluid connection to this inlet, the pressure at the inlet was the same as that measured at the end of the tube in the bottle.

Figure II shows the flow system used in this experiment. The components of this system are:

(A) High pressure regulator and reducer

(B) Low pressure regulator and reducer

(C) Mercury manometers

(D) Pyrex bottle fluid reservoir

(E) Valve for purging fluid system

(F) Synthetic core

(G) Valve and spigot at outlet

(H) Manometer connections

(I) Graduate

(J) Screen type filter

For the runs made in the vertical position essentially the same set up was maintained and a correction was made for the difference in height of the inlet to the core and the point where the pressure was measured in the bottle.

From Figure II it can be seen that the flow system consists only of applying air pressure to the bottle (b) which causes the fluid in the bottle to flow through the filter to the inlet of the core, then passing through the core to the outlet where it is caught and measured in the 500 cubic centimeter graduate (I).

The apparatus used to measure the per cent of sugar in the effluent stream was a Spencer Abbe-type Refractometer. This refractometer is accurate to the third decimal place. From the knowledge of the amount of sugar in the effluent stream the per cent of original fluid could be calculated.

CHAPTER VI

EXPERIMENTAL PROCEDURE

After completing the partial consolidation and drying of the core, a series of permeability tests were run with air. On the completion of the permeability tests porosity was obtained by two different methods. When the permeability and porosity were deemed satisfactory the core was saturated with water and connected to a fluid system that was under a controlled pressure. Thus the water in the core could be displaced by another fluid which in turn could be displaced by another fluid. During these displacements, rate and composition of the effluent stream were measured.

Permeability Determinations

Upon running initial permeability test it was found that one end section of the core had a very low permeability compared to the other two sections. Upon removing the end plate it could be seen that a small hard plug had been formed in the center of the core. This plug appeared to extend into the core for only a few centimeters. Using a diamond saw approximately 6 centimeters was cut from the end of the core which was then squared by the use of fine emery cloth. This

resulted in a core 33.7 centimeters in length. When permeabilities were run on this core it was found to have an overall permeability of 3.92 darcies while the three sections had permeabilities of 3.81, 4.01, and 3.80 darcies. All of these permeabilities were determined in the usual manner using air. After the values were determined they were plotted against the reciprocal of the mean pressure at which they were obtained and extrapolated to an infinite pressure to correct for the Klinkenberg effect.

Porosity Determinations

Two methods were used to determine the porosity of the core. The first method was to build up a pressure in the core, record this pressure, then lower the pressure by metering out a known volume of air and again record the pressure. Applying the perfect gas law the volume of space the gas occupied in the core could be calculated. The total volume of the tube and fittings can be determined from their dimensions, thus the porosity determined. The average value found by this method was .337.

The second method used the difference in dry and wet weights of the core and was described in a previous section. The porosity by this method was found to be .307. This method was thought to be more accurate than the one using air, so it was used in all calculations.

Index of Refraction Measurements

The solutions used in this experiment were transparent, thus using the proper instrument the index of refraction could easily be measured. Since the per cent of sucrose in an aqueous solution is directly related to its index of refraction a measurement of this value could be converted easily to per cent of sucrose present.

In this work the index of refraction of both the original fluid in the core and of the displacing fluid were measured before a run was started. At regular intervals during the run index of refraction of the efflux was measured and with these values the per cent of the original fluid in the efflux could be calculated.

Experimental Runs

After the permeability and porosity determinations had been made on the core it was left saturated with distilled water which was displaced by an aqueous sucrose solution of known index of refraction. The pressure bottle was filled with distilled water, then connected to the air system and to the core by means of plastic tubing. (See Figure II.)

Next a pressure was applied to the system through the regulators which maintained this pressure constant. A valve at the outflow end of the core was opened allowing the original fluid in the core to be displaced by the sucrose solution. The volume of the displaced fluid and the rate of flow

of the effluent stream was measured and recorded at the same time the index of refraction of the effluent was obtained.

By referring to the tables in the Handbook of Chemistry and Physics (14), the per cent of sucrose by weight in the effluent was obtained. The temperature was measured and a correction applied to the above percentage. From another table in the handbook the amount of sucrose (grams per liter) was obtained. Since the same values were obtained for the original sucrose solution the amount of the original fluid present in the effluent could be calculated. These measurements and calculations were made at regular intervals during the displacement process.

EXPERIMENTAL DATA

TABLE I

RUN NUMBER I

Temperature, 27° C P = 650 mm.Hg.

Original Fluid (Distilled water) Displacing Fluid (Sugar Solution)

n_D = 1.3323 n = 1.3710

Viscosity = .8540 cp Viscosity = 1.96 cp

% sugar = 24.725

cu. cms. produced	n = efflux	Prest. Pore Volume	% Sugar in eff.	Wt. of sugar in eff.	% of Displacing fluid in efflux	% original fluid in eff.
800	1.3322					
900	1.3331	.962	1.4	14	5.17	94.8
950	1.3351	1.02	13.55	139	51.2	48.8
980	1.3369	1.09	21.00	225	86.5	13.5
975	1.3680	1.075	23.30	249	94	6.0
1000	1.3695	1.195	23.95	262	98.7	2.3
1050	1.3702	1.165	24.30	267	98.5	1.5
1150	1.3708	1.27	24.40	269	99.0	1.0
1200	1.3710	1.436	24.72	271	100	0

n = Index of refraction.

TABLE II

[illegible] 2

Temperature = 25° C P = 620 mm. Hg.

Original Fluid (Sugar Solution) Displacing Fluid (Distilled Water)

n = 1.3710 n = 1.3325

Viscosity = 2.00 cp Viscosity = .8937 cp

% Sugar = 24.72%

cu. cms. Produced	n = effluent	Cent. Pore Volume	% Sugar in eff.	Wt. of sugar in eff.	% Original Fluid in eff.
500	1.3710	.352	24.72	579	1.00
600	1.3708	.422	24.45	268	.462
650	1.3690	.712	23.40	236	.350
750	1.3640	.773	20.49	220.5	.316
900	1.3560	.853	16.67	154	.31
850	1.3521	.850	13.08	137	.307
950	1.3470	1.040	10.02	104	.308
1000	1.3442	1.105	8.27	83.6	.317
1150	1.3410	1.213	6.52	64.5	.359
1250	1.3400	1.343	5.43	50	.307
1400	1.3351	1.545	2.60	25	.093
1600	1.3338	1.770	.45	6.5	.044
1700	1.3337	1.878	0	0	0
1800	1.3325				

Table [illegible]

[illegible]

[illegible] mm. [illegible]

[illegible] cp [illegible] cp

[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]

TABLE III

RUN NUMBER 3

Temperature = 32° C P = 520 mm. Hg.

Original Fluid (Sugar Solution) Displacing Fluid (Distilled water)

n = 1.4088 n = 1.3335

Viscosity = 6.1 cp Viscosity = .8587 cp

% Sugar - 45.035

Cc. cum. Produced	n = efflux	Fract. Pore Volume	% Sugar in eff.	Wt. of sugar in eff.	% Original Fluid in eff.
0	1.4088				
200	1.4020	.241	45.05	241	1.00
400	1.4029	.464	40.51	333	.934
600	1.3922	.632	35.50	450	.754
850	1.3797		29.50	332	.614
900	1.3684	.682	21.04	236	.436
950	1.3594		16.09	181	.354
750	1.34	.773	11.15	115	.214
700	1.3472		9.87	102	.188
800	1.3451	.883	12.50	130	.240
950	1.3463	.982	9.42	90	.181
1000	1.3472	1.105	9.87	102	.188
1050	1.3465	1.197	10.72	111	.205
1350	1.3472	1.490	9.87	102	.188
1725	1.3429	1.905	7.02	72	.133
1875	1.3412				
2000	1.3387	2.210	4.2	43	.0784
2600	1.3363	2.870	1.9	19	.035
3300	1.3349	3.640			
3750	1.3335	4.140			

TABLE IV

ARC TUBE 4

Temperature = 25° C P = 250 mm. Hg.

Original Fluid (Sugar Solution) Displacing Fluid (Distilled Water)

n = 1.3910 n = 1.3325

Viscosity = 3.5 cp Viscosity = .0137 cp

% Sugar = 55.01%

cc. cmb. Produced	n = effluent	Rate cc/min.	Fract. Pore Volume	% Sugar in eff.	Wt. % sugar in eff.	% Original fluid in effluent
0	1.3910	4.5				
100	1.3910	4.6	.11			
200	1.3910	5.7	.221			
300	1.3910	6.02	.331			
400	1.3910	6.3	.442			
500	1.3910	6.6	.552	35.01	413	1.00
600	1.3705	7.3	.662	33.51	374	.783
650	1.3755	8	.717	27.51	303	.734
800	1.3635	8.6	.883	20.09	217	.525
900	1.3524	9.5	.993	13.22	138	.334
960	1.3400		1.000	10.37	113.5	.274
1000	1.3409	9.7	1.105	9.02	99	.238
1050	1.3457		1.160	8.07	91.5	.221
1120	1.3441	10	1.232	7.01	80	.193
1200	1.330	10.3	1.325	3.7	37	.0890
1300	1.330	10.3	1.435	3.7	37	.0896
1500	1.3371	10.5	1.655	3.1	31	.075
1600	1.3360	10.3	1.770	3.7	37	.0896
1700	1.3360	10.6	1.875	2.4	24	.0591
1800	1.3352	11.1	1.990	2.3	23	.0557
2050	1.3355	12.5	2.26	2.00	20	.0485
2300	1.3332	12.5	2.54	.45	45	.011

TABLE 7

RUN NUMBER 3

Temperature = 26° C P = 760 mm. Hg.

Original Fluid (Sugar Solution) Displacing Fluid (Distilled Water)

n = 1.3721 n = 1.3324

Viscosity = 2.06 cp Viscosity = .0737 cp

% sugar = 24.73%

cc. cm. Produced	n = effluxn	Rate cc/min.	Pract. Pore Volume	% sugar in eff.	Wt. of sugar in eff.	% original fluid in efflux
100	1.3715	37				
300	1.3711	42				
550	1.3710	62	.033	24.71	272.5	100
600	1.3700		.040	24.13	205	97.3
650	1.3609		.005	22.93	250.5	94.0
710	1.3651	58	.704	19.06	216	79.3
800	1.3518		.383	15.30	135.5	49.7
850	1.3493	61	.933	10.99	114.5	42.0
900	1.3465	62	.983	8.50	98.5	36.1
950	1.3450	62	1.048	6.50	89	32.3
1000	1.3436	61	1.105	6.00	82	30.7
1050	1.3454	61	1.160	5.6	81	33.4
1100	1.3435	61	1.21	7.5	77	28.3
1150	1.3430	60	1.27	7.15	73	26.8
1200	1.3413	61	1.323	5.50	61	22.4
1300	1.3394	60	1.435	4.70	48	18.0
1400	1.3377	64	1.545	3.50	36	13.2
1500	1.3344	68	1.655	1.34	13	4.8
1600	1.3328	65	1.779			
1700	1.3323	63	1.875			
1800	1.3325	64	1.980			

[illegible]

TABLE VI

RUN NUMBER 6
(Vertical Run - Upward)

Temperature = 30° C

P = 300 mm. Hg.

Original Fluid (Distilled water)

n = 1.3324

Viscosity = .0797 cp

Displacing Fluid (Sugar Solution)

n = 1.3500

Viscosity = 3.7 cp

% Sugar = 30.01%

Sq. cm. Produced	n = Effluent	Rate cc/min.	React. Zone Volume	% Sugar in eff.	Wt. of sugar in eff. g/liter	% Oil-phase fluid in effluent
0		12				
100	1.3324	9½	.130			
200		8½	.221			
300		7	.350			
400	1.3324	6.7	.470			
500		5.1	.555			
600		4.6	.665			
700		4.2	.771			
800	1.3324	4	.860			
850	1.3324		.930			100
900	1.3330	3.7	.995	.30	4	99
910	1.3400		1.003	5.23	55	97.3
920	1.3408		1.014	9.71	102.5	75.5
930	1.3509		1.025	15.98	201	51.6
940	1.3811		1.042	30.50	344.5	17
950	1.3855		1.055	33.05	393	7.7
960	1.3890		1.064	34.05	401.5	3.5
980	1.3895		1.080	35.15	404	2.6
1000	1.3900	3.2	1.103	35.40	405	1.5
1025	1.3900					
1050	1.3900					
1100	1.3900	3.2	1.21	35.59	415	

TABLE VII

RUN NUMBER 7
(Vertical Run - Down)

Temperature = 26° C P = 225 mm. Hg.

Original Fluid (Sugar Solution) Displacing Fluid (Distilled Water)

n = 1.3902 n = 1.3304

Viscosity = 3.7 cp Viscosity = .0797 cp

Sugar = 35.01%

cm. cub. Produced	n = efflux	Mic	Fract. Pore Volume	% Sugar in eff.	Mt. of sugar in eff.	% Original fluid in efflux
50	1.3900	3.6	.0551			
100	1.3900	4.2	.11			
200	1.3903	4.5	.221			
300	1.3900	4.6	.331			
400	1.3900	4.7	.442			
500	1.3900	4.5	.552	35.09	415	100
555	1.3945		.612	32.33	365	85.6
570	1.3790		.629	29.78	355.5	80.3
600	1.3767	5.7	.662	27.03	311.5	75.0
650	1.3704		.728	24.31	265.0	64.6
700	1.3654	6.4	.773	21.36	232	55.9
755	1.3550		.832	18.37	190	45.4
800	1.3600	6.7	.883	16.01	193	46.5
850	1.3600		.938	13.14	154	46.5
900	1.3590	7.0	.993	10.78	179	43.2
950	1.3550		1.0550	12.59	165	39.8
1000	1.3522	7.0	1.100	13.14	139	33.5
1055	1.3490		1.165	11.09	122.5	29.5
1100	1.3403	7.5	1.215	10.69	111.5	27.7
1150	1.3400		1.270	9.69	100.5	24.1
1200	1.3400	7.6	1.270	9.14	94.5	22.9
1300	1.3437	8	1.325	7.03	79	19.0
1400	1.3411		1.435	5.86	69	14.2
1500	1.3397	8.5	1.545	4.20	44	10.6
1600	1.3372		1.655	3.36	32.5	7.8
1700	1.3343	9.5	1.770	1.46	15	3.6
1900	1.3330		1.990	.4	4	.91
2000	1.3325	10.4	2.1	.4	4	.91
2050	1.3321	10.4	2.210			

.11
.221
.331
.442

TABLE VIII

RUN NUMBER 8
(vertical Run - Upward)

Temperature = 27° C | P = 520 mm. Hg.

Original Fluid (Distilled water) | Displacing Fluid (Sugar Solution)

n = 1.3325 | n = 1.3700

Viscosity = .8545 cp | Viscosity = 1.75 cp

% Sugar = 24.75%

Cu. cm. Produced	n = effluent	Rate cc/min.	Fract. Pore Vol.
0		12	
100	1.3320	10.0	.11
200		9.3	.221
300		8.0	.332
400		5	.442
500		7.1	.552
700		5.8	.773
800		5.5	.883
800	1.3340	4.2	.993
925	1.3400		1.03
950	1.3500	4.0	1.08
975	1.3690		
1000			
1025	1.3700	4.5	1.13
1050	1.3700		

[illegible]

TABLE IX

[illegible] 2

Temperature = 27° C P = 220 mm. Hg.

Original Fluid (Sugar Solution)
n = 1.3702
Viscosity = 1.00 cp
% Sugar = 24.7[illegible]

Displacing Fluid (Distilled Water)
n = 1.3343
Viscosity = .8543 cp

cu. cm. Produced	n = effluent	Rate cc/min.	Frac. Pore Volume	% Sugar in eff.	Wt. Sugar in eff.	% Original fluid in eff.
100	1.3709	4.5				
200	1.3709	4.5				
300	1.3709	4.6				
500	1.3708	4.6				
550	1.3700	4.8				
600	1.3702	5.0	.662			
610	1.3703	5.0	.673	24.00	272.5	100
625	1.3695	5.0	.690	23.63	268	98
650	1.3679	5.1	.717	22.68	250.4	92
700	1.3654	5.2	.773	21.43	233	85.5
750	1.3629	5.2	.827	19.65	201	73.9
800	1.3577	5.2	.883	16.73	178	65.4
850	1.3543		.938	14.91	158	58.0
900	1.3507	5.4	.993	12.26	128	47.0
950	1.3469-		1.048	11.16	116	42.6
1000	1.3466	5.6	1.103	9.61	99	36.3
1050	1.3437		1.160	7.73	79.3	29.0
1150	1.3395	5.7	1.269	4.43	44	16.1
1200	1.3378	5.7	1.324	3.73	37.4	13.7
1650	1.3320	5.2	1.820			
1900	1.3343		1.976			

[illegible]

TABLE X

[illegible] 10

Temperature = [illegible]° C P = [illegible] mm. Hg.

Original Fluid (Distilled Water)
n = 1.3324
Viscosity = .0739 cp

Displacing Fluid (Sugar Solution)
n = 1.3365
Viscosity = 1.0 cp
% Sugar = 4.1%

Gal. Gas. Produced	n = effluent	Flow cc/min.	Effect. Pore Vol.
100	1.3324	13	.11
200	1.3324	13	.221
300	1.3324	12	.331
400	1.3324	11	.443
500	1.3324	10.3	.552
600	1.3324	10	.663
700	1.3324	9.9	.773
800	1.3324	9.5	.883
850	1.3324	9.3	.933
900	1.3370	8.9	.993
950	1.3372		1.039
1000	1.3373	7.9	1.105
1100	1.3362		1.21
1400	1.3365		1.545

[illegible]

TABLE XI

FOR [illegible] 11

Temperature = 25° C

P = 220 cm. Hg.

Original Fluid (Sugar Solution)

Displacing Fluid (Distilled Water)

n = 1.3395

n = 1.3324

Viscosity = 1.0 cp

Viscosity = .0737 cp

% Sugar = 4.16

Cu. cms. Produced	n of effluent	Rate cc/min.	Fract. Pore Volume	% Sugar in eff.	Vol. of sugar in eff.	% Orig. Fluid in eff.
400	1.3355	10.5				
700	1.3335					
800	1.3335	10.7	.803	4.16	42	1.00
850	1.3335		.938	4.16	40	1.00
890	1.3343	10.7	.972	2.06	23	.67
900	1.3343		.985	1.96	15	.31
925	1.3340		1.02	1.06	11	.26
975	1.3335		1.075	.71	7	.17
1000	1.3320	10.7	1.105	.35	3.6	.000
1050	1.3326		1.160			
1150	1.3324	10.7	1.210			

[illegible]

[illegible]

[illegible]

[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]

TABLE XII

CONTROLS DATA

Viscosity Ratio Displacing Fluid / Original Fluid	Pore Volume Produced at Complete Recovery	Per cent of Orig. Fluid Recovered at One Pore Volume	Index of Refraction of Total Displaced Liquid
.110	4.1	72.7	1.3320
.250	2.0	65.8	1.3520
.405	1.37	69.7	
.375	1.45	63.7	1.3321
4.25	1.2	53.0	

[illegible]

[illegible]

[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]
	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]
	[illegible]	[illegible]	[illegible]

F13782

FIGURE I



A LINEAR ENCROACHMENT SYSTEM
AFTER MUSKAT

FIGURE II



FLUID FLOW DIAGRAM


Figure III
Brine Concentration versus Volume Produced
(Horizontal Runs)
Viscosity Ratio = 1/2.41
Viscosity Ratio = 1/4.18
Viscosity Ratio = 1/7.24
Viscosity Ratio = 1/12.55
Viscosity Ratio = 1/21.75
Percent Original Fluid in Efflux
100
90
80
70
60
50
40
30
20
10
0
.4
1.0
2.0
3.0
4.0
Fraction of Pore Volume Produced


FIGURE IV
EFFLUX COMPOSITION VS PORE VOLUME PRODUCED
(Vertical Runs)
Viscosity Ratio - 1/4.25
Viscosity Ratio - 1/6.34
Viscosity Ratio - 1/7.21
Percent Original Fluid in Efflux
100
90
80
70
60
50
40
30
20
10
0
.3
.5
1.0
1.5
2.0
Fraction of Pore Volume Produced


Figure V
Effect of Pressure on Displacement
(Viscosity Ratio-1/2.24)
o Pressure = 220 mm Hg.
Δ Pressure = 760 mm Hg.
Percent Original Fluid in Error
100
90
80
70
60
50
40
30
20
10
0
.5
1.0
1.5
Fraction of Pore Volume Produced


Figure VI
Effects of Gravity
Pressure 226 mm Hg
Viscosity Ratio 1/4.23
Vertical Run
Horizontal Run
Percent Original Fluid in Efflux
Fraction of Pore Volume Produced
100
90
80
70
60
50
40
30
20
10
0
.5
1.0
1.5
2.0
2.5


FIGURE VII
Rate vs Pore Volume Produced
Viscosity Ratio 1/1.25
Viscosity Ratio 1/1.25
Rate - cc/min.
Fraction of Pore Volume Produced
0
1
2
3
4
5
6
7
8
9
10
11
.5
1.0
1.5


Figure VIII
Rate vs Pore Volume Produced
Viscosity water 1.12 c/s
Viscosity brine 1.16 c/s
Rate - cc/min.
Fraction of Pore Volume Produced
0
.5
1.0
1.5
1
2
3
4
5
6
7
8
9
10
11
12
13


FIGURE 10
PERCENT OF ORIGINAL FLUID
RECOVERED AT ONE PORE VOLUME
VS
VISCOSITY RATIO
Viscosity Ratio
3
2
1
0
70
75
80
85
90
95
100
Percent Original Fluid Recovered One Pore Volume


FIGURE 2
FRACTION OF PORE VOLUMES PRODUCED AT BREAKTHROUGH
VS
VISCOSITY RATIO
Vertical Rods
Horizontal Rods
Viscosity Ratio
10
9
8
7
6
5
4
3
2
1
.9
.8
.7
.6
.5
.4
.3
.2
.1
.3
.4
.5
.6
.7
.8
.9
1.0
Fraction Pore Volume Produced at Breakthrough


FIGURE 14
DISPLACEMENT EFFICIENCY DURING INITIAL PHASE
COMPARED TO DATA FROM LEVERETT AND BUCKLEY
Leverett and Buckley Data
Experimental Data
Fraction Original Fluid Displaced During Initial Phase
1.0
.9
.8
.7
.6
.5
.4
.3
0
1
2
3
4
5
6
7
8
9
10
Viscosity Ratio - Orig. Fluid/Disp. Fluid



FIGURE XII

Pore volumes produced at complete recovery
vs
viscosity ratio

(horizontal axis)


FIGURE XIII
PORE VOLUMES PRODUCED AT COMPLETE RECOVERY
VS
VISCOSITY RATIO
Viscosity Ratio
1.0
.9
.8
.7
.6
.5
.4
.3
.2
.1
1
2
3
4
5
6
7
8
9
10
Pore Volumes Produced at Complete Recovery


FIGURE XIV
AQUEOUS SUCROSE SOLUTION
VISCOSITY CURVE
25°C. & 30°C.
Viscosity - cp
100
90
80
70
60
50
40
30
20
10
9
8
7
6
5
4
3
2
1
0
10
20
30
40
50
60
70
Percent Sucrose in Solution

CHAPTER VII

ANALYSIS OF DATA

Theoretical Approach

An equation expressing the behavior of two miscible fluids of different viscosities, in the case of linear displacement, has been derived by Muskat (12). In developing this equation he simplified the system to one in which the two fluids are moving in a channel of small cross-sectional area compared to its length. This would be approximated physically by a narrow channel of high permeability. Figure 1 illustrates such a linear system.

For a system as shown in Figure 1 Muskat arrives at the following equation:

$$\left(\frac{\mu_2}{\mu_1} - 1\right)\left[\frac{\mu_2}{\mu_1}(1-\epsilon) + \epsilon + 1\right]\frac{2\Delta\Phi C_1 k}{L^2} = 0; \qquad \text{Equation (1)}$$

Where: k = permeability

p = pressure

Φ = potential function = kp if gravity is neglected

μ = viscosity

κ = fluidity = $1/\mu$

Δ = length

t = time

$\Delta\Phi$ = difference in potential function existing at the two boundaries.

$$\epsilon = \frac{C_1}{C_2} = \frac{\mu_2}{\mu_1}$$

L = linear distance flood front has traveled.

Since t is included in the combined term $\frac{2\Delta\Phi C_1 t}{L^2} = 0$, it shows that at any particular state of the displacement the time necessary to reach this state varies directly with the viscosity of the displaced fluid, directly as the total length of the system and inversely as the average potential gradient $\frac{\Delta\Phi}{L}$. From this it is seen that as the interface advances its rate of advance is accelerated if the displacing fluid has the higher fluidity ($\epsilon < 1$) whereas it is retarded if the displacing fluid has the lower fluidity ($\epsilon > 1$).

The total time for the interface to travel the total length is given by setting x_3 equal to zero in equation one and solving for $t_{max.}$:

$$t_{max.} = \mu_1 (1 + \mu_2/\mu_1) \frac{fL^2}{2\Delta\Phi} \qquad \text{Equation (2)}$$

where f is the porosity of the medium.

From this relation it is evident when $\mu_2 < \mu_1$ the displacement time is less than that for a single fluid.

$$t_{max.}^{\circ} = \frac{\mu_1 f L^2}{\Delta\Phi} \qquad \text{Equation (3)}$$

It may also be noted that when μ_2 is very much smaller than

μ_1 a maximum decrease in $t_{max.}$ is attained, thus in this limiting case the drive by a displacing fluid of very low viscosity would cut by half the time required for the column of original fluid to pass through the system. When $\mu_2 > \mu_1$ it can be seen that $t_{max.}$ will always exceed $t_{max.}^{o}$, and will ultimately become infinite as μ_2 becomes infinitely large.

Sample Calculations

In all of the experiments the only physical properties of the solutions measured were temperature and index of refraction. From these two measurements could be calculated the amount of sucrose in the solution and thus the fraction of the original fluid in the effluent stream.

As an example one calculation is shown for converting the index of refraction to fraction of original fluid in the effluent. Data is taken from Run No. 2, Table III, when 600 cc of fluid had been displaced.

Taking the index of refraction 1.4000 at 25° C, for the original fluid in the core, and referring to the table, "Index of refraction of Aqueous Solutions of Sucrose," in the Handbook of Chemistry and Physics, the per cent of sucrose was determined for a temperature of 20° C. to be 44.6. A temperature correction of + .42 was applied giving a per cent by weight of 45.03. From the table, "Specific Gravity of Aqueous Sucrose Solutions," in the same reference it was determined that this per cent of sucrose equals 541.3 grams per liter.

μ_1

$\mu_2 > \mu_1$

μ_2

When 800 cc of fluid had been displaced from the core the index of refraction of the effluo was measured and found to be 1.3620 at a temperature of 25° C. From the Handbook of Chemistry and Physics the corrected per cent of sucrose was determined to be 18.32 and the weight of sucrose in grams per liter 130. To get the fraction of the original fluid present in the effluent stream the following relation is used:

$$\text{Fract. of Orig. Fluid in Eff.} = \frac{\text{g./ltr. sucrose in effluo}}{\text{g./ltr. sucrose in Orig. Fluid}}$$

Substituting the above values gives:

$$\text{Fract. of Orig. Fluid in Eff.} = \frac{130.0}{541.5} = .240$$

Discussion of Experimental Results

The results obtained in this series of experiments are tabulated in Tables I through XII. These tables have been simplified by including only the pertinent data. In addition the original data contained index of refraction of the total solution displaced and total elapsed time, which were not used in this work. In Runs 1 through 3 the rate of flow was not recorded and in Run 9 the screen at the inlet end of the core became plugged and thus the rates recorded during this run were of no benefit.

All runs were made with the core in a horizontal position except runs number 6, 7, 8, 9. The core was placed in a vertical position for these runs. When a heavy fluid was displaced by a lighter fluid, the lighter fluid was introduced at the upper end of the core; if a light fluid was being displaced

by a heavier fluid it was introduced at the lower end of the core. Thus it was felt that the results of these drives were free from all effects of gravity.

Figures III and IV illustrate graphically the results of eight runs carried out at various viscosity ratios. Viscosity ratio as used in this paper will be the viscosity of the displacing fluid divided by the viscosity of the original fluid unless otherwise noted.

Figure III presents the results of the horizontal runs for various viscosity ratios. When the viscosity ratio is small as shown by the plot for a viscosity ratio of 1/3.2 the displacing fluid breaks through before half a pore volume has been produced. Following this break through there is a fairly constant decrease in the amount of original fluid in the effluent until approximately .5 of a pore volume is produced. From this point to a production of 1.6 pore volumes there appears to be unstable producing conditions as evidenced by the scattered points on the plot. The curve then tends to level off with very slight decrease in the amount of original fluid in the effluent. This appears to form a plateau on the plot. It is possible that this could be caused by gravity segregation since there was definite evidence of this when the progress of the flood front was followed visually as it moved along the core. The heavier fluid appeared to channel along the bottom of the core. When the core was rotated to check the possibility that the permeability was greater along

one side of the tube, the channeling effect was still along the bottom indicating that it could be caused by gravity.

Referring again to Figure III when the viscosity ratio approached unity or larger, as illustrated by the plot for a ratio of 1/1.14, the displacing fluid does not break through until over .6 of a pore volume is produced. The amount of original fluid in the effluent drops off rapidly with no apparent plateau in the curve. This should follow if the plateau is due to gravity segregation.

Similar runs were made with the core in a vertical position and the results plotted in Figure IV. From this it can be seen that the fraction of original fluid produced at break through is essentially the same as in the horizontal runs and thus is not appreciably affected by gravity. There was no indication of a plateau with a viscosity ratio as low as 1/4.22 which bears out the supposition that this leveling off, in the cases illustrated in Figure III, was caused by gravity segregation.

From Figures III and IV it would appear that the mechanics of displacement involving two miscible fluids is similar to that of two immiscible liquids as described by Buckley and Leverett (10). The displacement can be divided into two phases. The initial phase occurs before the break through of the displacing fluid and is a piston like displacement. In the subordinate phase, which follows the break through, the original fluid is produced by a dragging action.

this phase differs in the case of miscible fluids only in that 100 per cent of the original fluid can be produced which is not possible with immiscible fluids.

As a check on the accuracy of the plots and on the completeness of recovery of the original fluid from the core the area under each curve was measured. With 100 per cent recovery of the original fluid the area under each curve should be 100 units. In all cases the error was never more than 2 per cent.

The cause of the period of unstable production is not known, though it would seem possible that it could be due to streaks of variable permeability which would allow by-passing of small areas. At a later time the original fluid from these areas would reach the outlet end of the core and temporarily increase the amount of original fluid in the effluent.

To see what effect pressure would have on the displacement picture two runs were made using a viscosity ratio of 1/2.44. The pressure differential for one run was 250 mm. mercury and for the other run was 760 mm. mercury. The results plotted in Figure 9 show that an increase in pressure tends to cause a break through to occur earlier and to require more pore volumes before complete displacement of the original fluid takes place.

To study the possible effects of gravity segregation, runs were made with the core both in the horizontal and

vertical positions. Two runs with a viscosity ratio of 1/2.25 were plotted in Figure VI. From this plot it can be seen that in the horizontal run where it is possible for gravity segregation to take place the curve is not as simple or smooth as the curve for the vertical run. However, the vertical run does break through earlier than the horizontal run, but the piston, shows up in the horizontal run thus requiring more pore volumes through-put before complete displacement takes place.

Though it is not included herein, a similar plot for a viscosity ratio of 1/2.44 shows similar deviations between the two curves.

According to Muskat (15) the effect of viscosity ratio on the rate of flow of the effluent can be calculated by Equation (1). If the original fluid is being displaced by one of lower viscosity the overall resistance of the system will be lowered and the rate of efflux increased. If the original fluid is displaced by one of higher viscosity the overall resistance is increased and the rate of efflux decreased.

From Figure VII it is noted that there is an appreciable increase in efflux rate as soon as injection of the lower viscosity fluid commences. This increase in efflux rate tends to gradually drop off until the point is reached where the displacing fluid breaks through. Then there is a sharp increase in efflux rate with an immediate tapering off

of the rate till the point is reached where the original fluid is completely displaced and the efflux rate is constant.

This behavior is similar to the qualitative description given concerning the nature of the effects of the viscosity difference between overrunning and displaced liquids in the case of direct drive by Muskat (15). This should follow since the injection of the displacing fluid into a small opening in one end of a long cylindrical core and producing from a small opening in the other end would in many ways approximate the physical conditions of a direct drive between two walls.

The same pattern is shown by Figure VIII except in this case the original fluid is being displaced by one of higher viscosity, thus there is a decrease in efflux rates in place of an increase. The curve for a viscosity ratio of 1.34/1 was affected by a plugging of the screen at the inlet end of the core during the run. However, it was included since it illustrates the qualitative description given by Muskat.

To indicate a measure of the efficiency of the various drives as a function of the viscosity ratio, Figures IX, X, and XI were constructed. Figure IX illustrates the efficiency of recovery when one pore volume of fluid has been displaced from the core. From this it can be seen that as the viscosity ratios become smaller than .8 the per cent of original fluids displaced, when one pore volume has been produced, falls off

rapidly. With the viscosity ratio unity or larger there is very little increase in the per cent of original fluid displaced. Thus it can be seen that as long as the viscosity ratio is .5 or greater 90 per cent or more of the original fluid will be displaced when one pore volume has been produced.

As another measure of the efficiency of displacement, the pore volume produced when the displacing fluid breaks through was plotted against the logarithm of the viscosity ratio in Figure 2. This plot appears to give a straight line up to a viscosity ratio of .4 with a break from this point to a viscosity ratio of approximately .6. At this point there was a return to linearity but at a new slope. Unfortunately runs were not made with viscosity ratios in the region of departure from linearity so that information on this region is missing. It would seem, as indicated by Figure 10, when the viscosity ratio is .5 or greater that the recovery efficiency would be very high.

Figure 11 shows a plot of pore volumes of original fluid produced during the initial phase versus viscosity ratio, where the viscosity ratio is equal to the viscosity of the original fluid divided by the viscosity of the displacing fluid. For comparison data given by Buckley and Leverett (10), concerning the effect of oil viscosity on the efficiency of the initial phase of a water flood in a typical sand, is also plotted in the same figure.

The shape of the two curves in the above plot is

similar; however, the effect of viscosity ratio is greater in the case of miscible fluids. This might be explained by the fact that in the case of immiscible fluids all of the original fluid is not active and is not moved at any time during the displacement; thus limiting the range of the fraction of original fluid that could be displaced during the initial phase.

Figures XII and XIII give the number of pore volumes required before complete recovery of the original fluid is obtained. Figure XII indicates that the number of pore volumes required for complete recovery, for a viscosity ratio of .2 or greater, would be slightly larger than one. The number of pore volumes required as the viscosity ratio gets smaller does not decrease rapidly until a viscosity ratio of .4 is reached. From here the increase is very great even with only slight reductions in viscosity ratio.

The same data plotted on log paper gives a straight line with viscosity ratios of .3 or lower.

Referring to the article, "Some Experiments on the Mobility of Interstitial Waters" (13), where data is contained on the displacement from a sandstone core of radio active water by non active water the following conclusions are given: the displacing fluid breaks through when between .6 and .9 of a pore volume has been produced, 50 to 60 per cent of the original fluid was recovered when one pore volume had been produced, and over 1.5 pore volumes were produced before complete recovery of the original fluid occurs.

The data obtained during the present series of experiments, for a viscosity ratio comparable to that used in arriving at the results described above, does not check the above conclusions. This data indicates that over 80 per cent of the original fluid is produced before the displacing fluid begins through, approximately 95 per cent of the original fluid is displaced when one pore volume has been produced, and less than 1.2 pore volumes are required for complete recovery of the original fluid.

Thus even greater mobility of the interstitial water is indicated than was shown in the previous experiment. This could be due to the higher permeability that undoubtedly existed in this experiment but it would not seem that this alone would account for this difference.

It would appear that the shape of the displacement curves, Figures III and IV could be useful in studying the mechanism of displacement. Equation 2 indicates that the shape of the displacement curves might be an indication of the degree of permeability variation present in the porous media. However, work done by Cooper and Brown (16) displacing one fluid by another in a pipe line indicates that the shape of the displacement curves is a result of the parabolic interface formed in each of the capillary openings.

It would seem possible that the shape of the displacement curves could be affected by both of the above factors.

Errors Involved

The use of a refractometer to measure index of

refraction which in turn is converted to per cent of sucrose in an aqueous solution limits the accuracy of the results to the accuracy of the instrument used. In this work a Spencer Abbe-type refractometer was used. The scales on it could be read directly to the third decimal place and the fourth estimated with an accuracy of 0.0002. This gave an accuracy of 0.2 per cent in measuring the per cent of sucrose in solution.

The accuracy of the refractometer was checked before any runs were made by use of the glass test slab included with the instrument for which the index of refraction was known.

Index of refraction and viscosity of the solutions are both affected by changes in temperature. Since the temperature seldom changed more than a degree during a series of measurements it was felt that any temperature effects were within the experimental error. No appreciable effects on the data were observed that could be attributed to changes in temperature.

A small error was certainly introduced in the measurement of pressure differentials with a liquid manometer and volumes displaced with a graduated cylinder since there is some human error in reading fluid levels. These readings are considered to be well within the range of experimental error and sufficiently accurate for the computations necessary in this work. The degree of accuracy of these readings is indicated by graphical integration of the areas under the curves drawn in Figures III and IV. The majority of these areas were in error by less than one per cent and all were less than two per cent.

CHAPTER VIII

SUMMARY

A study was made of the displacement of one miscible fluid by another from a partially consolidated synthetic sandstone core. This core was composed of 30 to 140 mesh Oil Creek silica sand and colloidal silica. The porosity of the core was 20.7 per cent and the air permeability was 3.02 darcies. This core 6.35 centimeters in diameter and 23.7 centimeters in length was assembled with pressure taps in each end plate to permit determination of pressure drop across the core. The core was saturated with a fluid of known viscosity, then this fluid was displaced by another miscible fluid of different viscosity. The rate of efflux, total amount of fluid produced, and data to calculate the per cent of original fluid in the efflux was measured and recorded at regular intervals.

The solutions used in these experiments were made by dissolving various amounts of cane sugar (sucrose) in distilled water. The amount of sucrose in solution determined the viscosity of the fluid. Four solutions were used plus distilled water to get a range of viscosity ratios. The four

solutions contained 4.1, 14.6, 32.1, and 47.03 per cent of sucrose by weight.

Since information of a fundamental nature was sought it was decided to vary only the viscosity ratio of the displacing fluid to the original fluid and to maintain all other factors as nearly constant as possible. The range of viscosity ratios examined in these experiments ran from .11 to 9.1.

The data gathered in this work was used to arrive at several conclusions regarding the effect of viscosity ratio on the mechanics and the efficiency of displacement of one miscible fluid by another.

CHAPTER IX

CONCLUSIONS

1. The mechanics of the displacement of one miscible fluid by another is similar to the mechanics of displacement where the two fluids are immiscible. The displacement can be divided into two phases, the initial phase where there is a piston like displacement and the subordinate phase where the fluid is displaced by a dragging action.

2. When the viscosity ratio is smaller than unity the rate will increase, if the viscosity ratio is larger than unity the rate will decrease.

3. Increasing pressure differential and maintaining the same viscosity ratio causes the break through of the displacing fluid to occur earlier and requires more pore volumes to obtain complete displacement of the original fluid.

4. If gravity segregation is present more pore volumes will be required to obtain complete recovery.

5. Efficient displacement in the initial phase is obtained with viscosity ratios of .5 or greater. More than 90 per cent of the original fluid is recovered when one pore volume has been produced.

CHAPTER IV

CONCLUSIONS

1. The conclusions of the distinguishers of the variable state is confusing in relation to the concepts of distinguishers because the two states are isomorphic. The distinguishers can be divided into two groups, the initial phase where there is a phase line distinguisher and the subsequent phase where the state is distinguished by a complex matrix.

2. When the viscosity ratio is greater than unity the phase will disappear if the viscosity ratio is larger than unity the case will happen.

3. Considering pressure differential and interfacial the case viscosity ratio remains the same. Depends on the dimensionless group by which scaling and analysis have been performed by which every the distinguishers of the original model.

4. If gravity considerations is ignored such phase phase relations will be employed in which computer programming.

5. Initial disturbance in the initial phase is amplified with viscosity ratios of 4.5 or greater. This time is far shorter than the initial phase is considered when the viscosity and have considered.

6. For the most efficient complete recovery of original fluid the viscosity ratio should be .3 or greater.

7. Viscosity ratios of .3 and lower do not produce efficiently in the initial phase and require 3 or more pore volumes for complete recovery.

8. There is very little increase in the efficiency of displacement when the viscosity ratio is increased beyond unity.

9. Further study to determine if a relation exists between the shape of the displacement curves and permeability variation is indicated in view of the importance of this factor in the production of petroleum.

BIBLIOGRAPHY

1. d'Arcy, H. Les Fontaines Publiques de la Ville de Dijon. Paris, 1856. Victor Dalmont.

2. Slichter, C. S. "Principles and Conditions of the Movement of Ground Water." U.S. Geological Survey, 19th Ann. Rept. (1899) pt. 2, [illegible].

3. Cloud, P. F. "Variation of Pressure Gradient with Distance of Gas-Free Flow of Gas-Saturated Oil and Under Saturated Oil Through Unconsolidated Sands." Trans. A.I.M.E. (1943) 56, 651-663.

4. Putting, T. G. "Movement of Fluids in Porous Solids." Oil and Gas Journal (Sep. 25, 1944) 24, 143.

5. Kyrofff, N. D., Botset, H. G., and Muskat, M. "Flow of Fluids Through Porous Materials Under the Action of Gravity." Physics (1934) 5, 98-113.

6. Leverett, M. C. "Flow of Oil-Water Mixtures Through Unconsolidated Sands." Trans. A.I.M.E. (1939-1940) 137-152, 601.

7. Leverett, M. C., and Lewis, W. B. "Steady Flow of Gas-Oil-Water Mixtures Through Unconsolidated Sands." Trans. A.I.M.E. (1940-1941) 146-164, 290.

8. Reid, L. S. and Huntington, R. L. "Flow of Oil-Gas Mixtures Through Unconsolidated Sand." Trans. A.I.M.E. (1943) 127, 222.

9. Botset, H. G. "Flow of Gas-Liquid Mixtures Through Unconsolidated Sand." Trans. A.I.M.E. (1940-1941) 136-142, 136.

10. Dunlap, H. F. and Leverett, M. C. "Mechanism of Fluid Displacement in Sands." Trans. A.I.M.E. (1942-1943) 140-171, 148.

11. Hertz, W. "Mixing of Gases in Porous Media." Thesis, Master of Chemical Engineering, University of Oklahoma, 1941.

[illegible]

1. [illegible] [illegible] [illegible]

13. Dodson, J. "Diffusion of Gases through Sand." Thesis, Master of Engineering, University of Oklahoma, 1953.

12. Dussel, G. C., Morgan, F., and Husler, H. "Some Experiments on Mobility of Interstitial Waters." T.P. 2084, Petr. Tech., July 1946.

14. Handbook of Chemistry and Physics. 44th Edition. Cleveland, Ohio: Chemical Rubber Publishing Co., 1962.

15. Muskat, M. The Flow of Homogeneous Fluids through Porous Media. Ann Arbor: J. W. Edwards, Inc., 1946.

16. Taylor, Frank C. and Brown, Geo. Granger. "Contamination by Successive Flow in Pipe Lines." Trans. A.I. Ch. E. (August 1943) 39-4.

APPENDIX



thesG55
A study of the effect of viscosity ratio
3 2768 001 03503 3
DUDLEY KNOX LIBRARY